

BETTER BY DESIGN

**UM5S
L5S**



UM5S MINEXTRA[®] L5S

Engineered to provide outstanding performance and reduced down-time in the harshest of conditions. Suitable for both transportation and haulage equipment. The smooth L5S tread design with it's re-enforced shoulder and side wall is ideal for haulage in the toughest of mining environments.

Suitable for the most extreme underground applications. Lower cost and increase productivity by providing an outstanding combination of protection, durability and traction resulting in; Lower equipment operating costs & Increased productivity. Maximum traction, performance, stability and improved operator comfort.

- Extra-deep tread
- Extra-thick, heavy-gauge steel crown & sidewalls
- Re-enforced shoulders
- Cut & Heat resistant rubber compounds
- Multiple heavy-duty steel belts
- Tough, repairable and re-treadable casings

UM5S L5S



maitech®
ALL STEEL RADIAL

SIZE	PATTERN	LOAD INDEX SPEED SYMBOL STAR MARKING	SPEED	TYRE LOAD LIMITS AT VARIOUS COLD INFLATION PRESSURES (100 KPA=1BAR) AND SPEEDS											
				KPa	325	350	375	400	425	450	475	500	525	550	575
				psi	47	51	54	58	62	65	69	73	76	80	83
17.5R25	UM5S MINEXTRA® L5S	182A2 **	10 Km/h	Kgs	6000	6150	6500	6700	7100	7300	7500	7750	8000	8250	8500
			5 m.p.h.	lbs	13200	13600	14300	14800	15700	16100	16500	17100	17600	18200	18700
20.5R25	UM5S MINEXTRA® L5S	193A2 **	10 Km/h	Kgs	8000	8250	8750	9000	9500	9750	10000	10300	10900	11200	11500
			5 m.p.h.	lbs	17600	18200	19300	19800	20900	21500	22000	22700	24000	24700	25400
23.5R25	UM5S MINEXTRA® L5S	201A2 **	10 Km/h	Kgs	10300	10600	11200	11500	12150	12500	12850	13200	13600	14000	14500
			5 m.p.h.	lbs	22700	23400	24700	25400	26800	27600	28300	29100	30000	30900	32000
26.5R25	UM5S MINEXTRA® L5S	209A2 **	10 Km/h	Kgs	12850	13200	14000	14500	15000	15500	16000	16500	17000	18000	18500
			5 m.p.h.	lbs	28300	29100	30900	32000	33100	34200	35300	36480	37500	39700	40800
29.5R25	UM5S MINEXTRA® L5S	216A2 **	10 Km/h	Kgs	15500	16000	17000	17500	18000	19000	19500	20000	20600	21200	22400
			5 m.p.h.	lbs	34200	35300	37500	38600	39700	41900	43000	44100	45400	46700	49400

SIZE	TYPE	RIM WIDTH		OUTSIDE DIAMETER	TYRE WIDTH	WIDTH LOADED	STATIC LOADED RADIUS	TREAD DEPTH
17.5R25	Tubeless	25-14.00/1.5	mm	1395	440	455	614	68
			in.	54.92	17.32	17.91	24.17	86/32
20.5R25	Tubeless	25-17.00/2.0	mm	1548	520	535	674	74
			in.	60.94	20.47	21.06	26.53	93/32
23.5R25	Tubeless	25-19.50/2.5	mm	1665	590	620	719	80
			in.	65.55	23.22	24.41	28.30	101/32
26.5R25	Tubeless	25-22.00/3.0	mm	1794	666	686	770	90
			in.	70.63	26.22	27.00	30.31	114/32
29.5R25	Tubeless	25-25.00/3.5	mm	1920	740	760	819	97
			in.	75.60	29.13	29.92	32.25	123/32

Maitech tyres conform to ETRTO, TRA & JATMA Standards.

Distributed by:

maitech®
ALL STEEL RADIAL

Uzmai International s.r.l. - Italy - Via Conche, 1151 - 37050 Isola Rizza VERONA
Tel. +39 045 6970505 Fax +39 045 6971377 - info@maitechtire.com - www.maitechtire.com