

Product name:

59U

Operating limits:

Pressure: 28 Bar

Speed: 13 m/s

Temperature: -30°C... + 200°C



Specifications:

Type	d1	d3	d7	L1	L3
59U 20	20	34	35	37.5	13.5
59U 22	22	36	37	37.5	13.5
59U 24	24	38	39	40	13.5
59U 25	25	39	40	40	13
59U 28	28	42	43	42.5	12.5
59U 30	30	44	45	42.5	12
59U 32	32	46	48	42.5	12
59U 33	33	47	48	42.5	12
59U 35	35	49	50	42.5	12
59U 38	38	54	56	45	13
59U 40	40	56	58	45	13
59U 43	43	59	61	45	13
59U 45	45	61	63	45	13
59U 48	48	64	66	45	13
59U 50	50	66	70	47.5	13.5
59U 53	53	69	73	47.5	13.5
59U 55	55	71	75	47.5	13.5
59U 58	58	78	78	52.5	13.5
59U 60	60	80	80	52.5	13.5
59U 65	65	85	85	52.5	13.5
59U 70	70	90	92	60	14.5
59U 75	75	95	97	60	45.5
59U 80	80	104	105	60	45
59U 85	85	109	110	60	45
59U 90	90	114	115	65	50
59U 95	95	119	120	65	50
59U 100	100	124	125	65	50

-  Stationary (Ceramic/SiC/TC)
-  Rotary (Carbon/SiC/TC)
-  O-Ring (NBR/EPDM/VITON)
-  Spring, Retainer, Push Ring (SUS304/SUS316)

