

Product name:

58U

Operating limits:

Pressure:	28 Bar
Speed:	13 m/s
Temperature:	-30°C... + 200°C



Specifications:

Type	d1	d3	d7	L1	L3
58U 14	14	24	25	35	12
58U 16	16	26	27	35	12
58U 18	18	32	33	37.5	13.5
58U 20	20	34	35	37.5	13.5
58U 22	22	36	37	37.5	13.5
58U 24	24	38	39	40	13.3
58U 25	25	39	40	40	13
58U 28	28	42	43	42.5	12.5
58U 30	30	44	45	42.5	12
58U 32	32	46	48	42.5	12
58U 35	35	49	50	42.5	12
58U 38	38	54	56	45	13
58U 40	40	56	58	45	13
58U 45	45	61	63	45	13
58U 50	50	66	70	47.5	13.5
58U 55	55	71	75	47.5	13.5
58U 60	60	80	80	52.5	13.5
58U 65	65	85	85	52.5	13.5
58U 70	70	90	92	60	14.5
58U 75	75	95	97	60	45.5
58U 80	80	104	105	60	45
58U 85	85	109	110	60	45
58U 90	90	114	115	65	50
58U 95	95	119	120	65	50
58U 100	100	124	125	65	50

-  Rotary Ring (Impregnated Carbon/SIC/TC)
-  Stationary Ring (Ceramic/SIC/TC)
-  ORING (NBR/EPDM/VITON)
-  Spring, Retainer, Push Ring (SUS304/SUS316)

