

Product name:

NT-GN

Operating limits:

Pressure: 5 Bar

Speed: 10 m/s

Temperature: -30°C... + 100°C



Specifications:

Type	d1	d2	d6	d7	L1	L3
NT-GN 8	8	16	13	18/21	18	7
NT-GN 9	9	20	16	21	23	7
NT-GN 10	10	20	16	20/22/24	23	7
NT-GN 11	11	20	16	24	23	7
NT-GN 12	12	22.5	17	26	24	7
NT-GN 13	13	22.5	17	26	24	7
NT-GN 14	14	24.5	21	28/30	25	7
NT-GN 15	15	24.5	21	28/30	25	7
NT-GN 16	16	28.5	22	32	27	8
NT-GN 17	17	28.5	22	32	27	8
NT-GN 18	18	31.5	25	35	29	8
NT-GN 19	19	31.5	25	35	29	8
NT-GN 20	20	33.5	27	38	31	8
NT-GN 22	22	34.5	29	40	32	8
NT-GN 25	25	37.5	32	44	33	9
NT-GN 28	28	40.5	34	46	34	9
NT-GN 30	30	44.5	38	50	35	9
NT-GN 32	32	47.5	40	54	37	9
NT-GN 35	35	50.5	44	58	40	10
NT-GN 38	38	53.5	46	60	42	10
NT-GN 40	40	56.5	48	64	43	10
NT-GN 45	45	61.5	52	66	45	10
NT-GN 50	50	66.5	58	72	47	10

-  Stationary Ring (Carbon/SIC/TC)
-  Rotary Ring (Ceramic/SIC/TC)
-  Secondary Seal (NBR/EPDM/VITON)
-  Spring and Other Parts (S.S./SUS304/SUS316)

