

Product name:

NT/PS

Operating limits:

Pressure: 12 Bar

Speed: 15 m/s

Temperature: -30°C... + 200°C



Specifications:

Type	d1	d3	d7	L1	L3
NT/PS 14	14	24.5	25	35	8
NT/PS 16	16	26.8	27	35	8
NT/PS 18	18	31.8	33	37.5	10
NT/PS 20	20	32.5	35	37.5	10
NT/PS 22	22	36.5	37	37.5	10
NT/PS 24	24	38.8	39	40	10
NT/PS 25	25	38.8	40	40	10
NT/PS 28	28	46.5	43	42.5	10
NT/PS 30	30	46.5	45	42.5	10
NT/PS 32	32	46.5	48	42.5	10
NT/PS 33	33	49.5	48	42.5	10
NT/PS 35	35	49.5	50	42.5	11
NT/PS 38	38	54	56	45	11
NT/PS 40	40	57	58	45	11
NT/PS 43	43	61.5	61	45	11
NT/PS 45	45	61.5	63	45	11
NT/PS 48	48	70.6	66	45	11
NT/PS 50	50	70.6	70	47.5	11
NT/PS 53	53	70.6	73	47.5	12
NT/PS 55	55	76	75	47.5	12
NT/PS 58	58	79.6	78	52.5	12
NT/PS 60	60	79.6	80	52.5	12
NT/PS 63	63	84.6	83	52.5	12
NT/PS 65	65	84.6	85	52.5	13

-  Rotary Ring (Carbon/SIC/TC)
-  Stationary Ring (Ceramic/SIC/TC)
-  Secondary Seal (NBR/EPDM/VITON)
-  Spring and Other Parts (S.S./SUS304/SUS316)

